

Technical Information

Part No.

013001xx – UX30 White

013002xx – UX30 Light Blue

01300Yxx – UX30 Other colors



11 Kompert St. Tel-Aviv, 66849, Israel • Tel: 972-3-5188728 • Fax: 972-3-5188729

Standard Smock UX30

- Static dissipative smock
- For use in EPA (Electrostatic Protective Area)
- IEC 61340-5-1 compatible
- 3/4 Unisex Design
- Easy snap fastening (hidden Nickel free snaps)
- One breast pocket with ESD logo
- Two hips pockets
- Carbon loaded Fibers in 4 mm grid
- All sizes available
- **All colors available**

■ Fabric:

SF30 – 63% Polyester, 34% cotton, 3% conductive fibers. 156 g/sm



Machine washable up to 60⁰ c
Do not bleach
Do not add acid or alkali

Durability

IEC61340-5-1 Electrical properties maintained after **more than 100** industrial launderings

Technical Information

Part No.

013001xx – UX30 White

013002xx – UX30 Light Blue

01300Yxx – UX30 Other colors



11 Kompert St. Tel-Aviv, 66849, Israel • Tel: 972-3-5188728 • Fax: 972-3-5188729

Electrical properties:

	Test standard	Typical values	Requirements
Point to point resistance Rp	IEC 61340-5-1	$10^5 - 10^7 \Omega$	$R_p \leq 10^{12} \Omega$
Decay time	IEC 61340-2-1	0.5-0.9 seconds Peak voltage $U \leq 150V$	< 2 seconds To 10% of initial value (max peak voltage 1000V)

