



Fabric Technical Data Sheet

Tel: 972-3-550 9148 | Fax: 972-3-550 7969 | Web: kk-fabrics.com | 15 HaSatat St, Holon 58856, Israel

Lady's Smock LS40

- Static dissipative lady's smock
- For use in EPA Electrostatic Protective Area
- IEC 61340-5-1 compatible
- Lady's Design 3/4 length
- Easy snap fastening, hidden Nickel free snaps
- One breast pocket with ESD logo
- Two hip pockets
- Carbon loaded fibers woven in 4 mm grid Double carbon loaded fibers on the weft
- All sizes available
- All colors available providing Pantone number
- Fabric:
- SF40 62% Polyester 34% cotton 4% conductive fibers
- Weight -156 g/sm
- Comfortable and breathable











Machine washable up to 40° c Do not bleach Do not use acid or alkali Ironing at Medium temperature Tumble dry at low temperature



Durability

IEC 61340-5-1 Electrical properties maintained after more than 100 industrial launderings





Fabric Technical Data Sheet

Tel: 972-3-550 9148 | Fax: 972-3-550 7969 | Web: kk-fabrics.com | 15 HaSatat St, Holon 58856, Israel

Electrical properties

	Test standard	Typical values	Requirements
Point to point resistance Rp	IEC 61340-5-1	10 ⁵ - 10 ⁷ Ω	$Rp \le 10^{11}\Omega$
Decay time	IEC 61340-2-1	0.5-0.9 seconds Peak voltage U ≤ 150V	< 2 seconds To 10% of initial value (max peak voltage 1000V)